

HG-CLAD METAL-SS



PRODUCT DESCRIPTION

HG-CLAD METAL-SS is a 24 ga (0.61 mm) stainless metal sheet. It has a 20 mil thermoplastic UV stable coating laminated on one side. The laminated thermoplastic membrane is completely compatible with all **HYDRO-PRUFE® PVC** membranes and flashing. **HG-CLAD METAL-SS** is durable and provides a finish look when left exposed in metal flashing applications. It can be sheared and break formed in a multitude of shapes for all types of applications.

PRODUCT NUMBERS AND COLORS

Standard Color is: White and Gray

Custom Colors: Available, contact **HYDRO-GARD** for custom colors

PACKAGING

<u>Sheets/Pallet</u>	<u>Size</u>	<u>Weight</u>	<u>Pallet/Weight</u>
25 ea	47" x 8 ft	42 lbs	1,100 lbs

RECYCLED CONTENT

Recycled Content of (Metal):	25% Post Consumer
Pre-consumer Content (Metal):	6% Pre Consumer
Thermoplastic Membrane:	0%

INSTALLATION

HG-CLAD METAL-SS can be cut to size and formed into any custom shape for all flashing applications. Heat welding **HYDRO-PRUFE®** membrane and flashing to **HG-CLAD METAL-SS** assures a complete water tight system. Joints are butt end to end and a 4" wide piece of **HYDRO-PRUFE®** flashing is welded over the butt joint. See **HYDRO-GARD** details for any additional information.

AVAILABILITY

HG-CLAD METAL-SS is available from the manufacturer, vendors, or factory trained contractors.

WARRANTY

When used as an accessory to the **Hydro-Prufe®** PVC waterproofing system it is inclusive in the **Hydro-Prufe®** waterproofing warranty.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

HYDRO-GARD LLC • 18340 Yorba Linda Blvd. Suite 107, Box 304, Yorba Linda, Ca 92886

Tel 562/ 944-7030 • Fax 562/ 944-6402 • www.hydro-gard.com