

HYDRO-TUFF® PB-25



PRODUCT DESCRIPTION

Hydro-Tuff® PB-25 is a SBS modified fiberglass base sheet used to be imbedded into the Hydro-Tuff® HFA membrane while the membrane is still warm and sticky. It is a lighter version of the Hydro-Tuff® protection layers. Hydro-Tuff® PB-25 is intended to be used as a protection material for the Hydro-Tuff® HFA when the direct overburden is insulation. It is not intended to be used when heavy overburden materials are used.

PRODUCT NUMBERS AND COLORS

Standard Color is: Black / with sanded surface

TYPICAL PROPERTIES

| <u>Description</u> | <u>Results</u> |
|--------------------|----------------|
| Roll Dimension | 39"W x 49' L |
| Square Feet | 161 sf |
| Roll Weight | 94 lbs |
| Weight per Square | 58 lbs |
| Thickness | 94 mils |

RECYCLED CONTENT

Pre Consumer Content 24.5%

PACKAGING

Pallet: 20 rolls
Truck Load: 400 rolls

INSTALLATION

The Hydro-Tuff® PB-25 is set in the warm and sticky Hydro-Tuff® HFA membrane. Overlap side and end laps a minimum of 3" and ensure laps are well adhered. Hydro-Tuff® PB-25 is not intended for high traffic areas. Cover with insulation as soon as possible and protect from UV degradation.

AVAILABILITY

Hydro-Tuff® PB-25 is available from the manufacturer, vendors, or factory trained contractors.

WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

MAINTENANCE

Hydro-Tuff® PB-25 requires no maintenance.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

HYDRO-GARD LLC • 18340 Yorba Linda Blvd. Suite 107, Box 304, Yorba Linda, Ca 92886

Tel 562/ 944-7030 • Fax 562/ 944-6402 • www.hydro-gard.com