

HYDRO-TUFF® PB-40



PRODUCT DESCRIPTION

Hydro-Tuff® PB-40 is a SBS modified fiberglass base sheet used to be imbedded into the Hydro-Tuff® HFA membrane while the membrane is still warm and sticky. It is a medium version of the Hydro-Tuff® protection layers. Hydro-Tuff® PB-40 is intended to be used as a protection material for the Hydro-Tuff® HFA. Contact manufacturer for specific applications.

PRODUCT NUMBERS AND COLORS

Standard Color is: Black / with sanded surface

TYPICAL PROPERTIES

<u>Description</u>	<u>Results</u>
Roll Dimension	39"W x 49' L
Square Feet	161 sf
Roll Weight	98 lbs
Weight per Square	60 lbs
Thickness	94 mils

RECYCLED CONTENT

Post consumer content	4.5% weight
Pre consumer content	24.5% weight

PACKAGING

Pallet:	20 rolls
Truck Load:	400 rolls

INSTALLATION

The Hydro-Tuff® PB-40 is set in the warm and sticky Hydro-Tuff® HFA membrane. Overlap side and end laps a minimum of 3" and ensure laps are well adhered. Hydro-Tuff® PB-40 is not intended to be exposed to prolonged periods of UV exposure. Consult with manufacturer for additional information.

AVAILABILITY

Hydro-Tuff® PB-40 is available from the manufacturer, vendors, or factory trained contractors.

WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

MAINTENANCE

Hydro-Tuff® PB-40 requires no maintenance.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

HYDRO-GARD LLC • 18340 Yorba Linda Blvd. Suite 107, Box 304, Yorba Linda, Ca 92886

Tel 562/ 944-7030 • Fax 562/ 944-6402 • www.hydro-gard.com