

# HYDRO-TUFF PB-50



## PRODUCT DESCRIPTION

Hydro-Tuff® PB-50 is a SBS modified fiberglass base sheet used to be imbedded into the Hydro-Tuff® HFA membrane while the membrane is still warm and sticky. It is a heavier version of protection of the Hydro-Tuff® protection layers. Hydro-Tuff® PB-50 is intended to be used as a protection material for the Hydro-Tuff® HFA. Contact manufacturer for specific applications.

## PRODUCT NUMBERS AND COLORS

Standard Color is: Black / with sanded surface

## TYPICAL PROPERTIES

<u>Description</u>	<u>Results</u>
Roll Dimension	39"W x 32' 9" L
Square Feet	100 sf
Roll Weight	88 lbs
Weight per Square	88 lbs
Thickness	120 mils

## RECYCLED CONTENT

Pre Consumer Content 16.6% weight

## PACKAGING

Pallet: 20 rolls  
Truck Load: 400 rolls

## INSTALLATION

The Hydro-Tuff® PB-50 is set in the warm and sticky Hydro-Tuff® HFA membrane. Overlap side and end laps a minimum of 3" and ensure laps are well adhered. Hydro-Tuff® PB-50 is not intended to be exposed to prolonged periods of UV exposure. Consult with manufacturer for additional information.

## AVAILABILITY

Hydro-Tuff® PB-50 is available from the manufacturer, vendors, or factory trained contractors.

## WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

## MAINTENANCE

Hydro-Tuff® PB-50 requires no maintenance.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit [www.hydro-gard.com](http://www.hydro-gard.com). HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

HYDRO-GARD LLC • 18340 Yorba Linda Blvd. Suite 107, Box 304, Yorba Linda, Ca 92886

Tel 562/ 944-7030 • Fax 562/ 944-6402 • [www.hydro-gard.com](http://www.hydro-gard.com)