

HYDRO-PRIMER LOW VOC



PRODUCT DESCRIPTION

Hydro-Primer Low VOC is a specially formulated cutback based asphalt primer that is used to improve adhesion for the HYDRO-TUFF HFA waterproofing membrane. The primer is applied to the concrete or masonry surfaces prior to the application of the HYDRO-TUFF HFA.

PRODUCT NUMBERS AND COLORS

Standard Color is: black

PHYSICAL PROPERTIES

<u>Description</u>	<u>Results</u>
% Solids by Weight	63-65 %
Brookfield Viscosity	<3000 cps
Flash Point	>105F°
Weight per Gallon	7.5-7.9 lbs
Dry to touch time @ 72F°	45 min
VOC content: grams/Liter	<350

PACKAGING

5 gallon pails or 55 gallon drums

INSTALLATION

Hydro-Primer Low VOC is installed by brush, roller or spray. The primer must be installed to clean and dry surfaces. Temperatures during application should range at minimum from 45° to 110°f. Application rate will depend on surface condition, porosity and texture. The application rate should range from 200 to 300 sf per gallon. Do not let primer puddle or pool. Excess primer can create loss of adhesion for the membrane. Let primer cure to the touch. Contact manufacturer for additional information.

AVAILABILITY

Hydro-Primer Low VOC is available from the manufacturer, vendors, or factory trained contractors.

WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

MAINTENANCE

Hydro-Primer Low VOC requires no maintenance.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

HYDRO-GARD LLC • 18340 Yorba Linda Blvd. Suite 107, Box 304, Yorba Linda, Ca 92886

Tel 562/ 944-7030 • Fax 562/ 944-6402 • www.hydro-gard.com