# **HG-CLAD METAL-G**



## **PRODUCT DESCRIPTION**

HG-CLAD METAL-G is a 24 ga (0.61 mm) galvanized metal sheet. It has a 20 mil thermoplastic UV stable coating laminated on one side. The laminated thermoplastic membrane is completely compatible with all HYDRO-PRUFE® PVC membranes and flashing. HG-CLAD METAL-G is durable and provides a finish look when left exposed in metal flashing applications. It can be sheared and break formed in a multitude of shapes for all types of applications.

## **PRODUCT NUMBERS AND COLORS**

Standard Color is: White and Gray

Custom Colors: Available, contact HYDRO-GARD for custom colors

## PACKAGING

Sheets/Pallet	Size	Weight	Pallet/Weight
25 ea	4 ft x 8 ft	35 lbs	905 lbs
25 ea	4 ft x 10 ft	44 lbs	1,130 lbs

#### **RECYCLED CONTENT**

Recycled Content of (Metal):25% Post ConsumerPre-consumer Content (Metal):6% Pre ConsumerThermoplastic Membrane:0%

## INSTALLATION

HG-CLAD METAL-G can be cut to size and formed into any custom shape for all flashing applications. Heat welding HYDRO-PRUFE® membrane and flashing to HG-CLAD METAL-G assures a complete water tight system. Joints are butt end to end and a 4" wide piece of HYDRO-PRUFE® flashing is welded over the butt joint. See HYDRO-GARD details for any additional information.

# AVAILABILITY

HG-CLAD METAL-G is available from the manufacturer, vendors, or factory trained contractors.

## WARRANTY

When used as an accessory to the Hydro-Prufe® PVC waterproofing system it is inclusive in the Hydro-Prufe® waterproofing warranty.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit <a href="http://www.hydro-gard.com">www.hydro-gard.com</a>. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.