

SAF-30 ADHESIVE



PRODUCT DESCRIPTION

SAF-30 ADHESIVE is a modified methacrylate liquid paste in tube form. It is primarily used as an adhesive to bond accessory products like the hydrophilic **Hydro-Gard Swell Tape** and **Waterstop B** to the **HYDRO-PRUFE® PVC** waterstop in compartmentalization design. It can also be used as a basic termination sealant for the **HYDRO-PRUFE® PVC** membrane.

PHYSICAL PROPERTIES

<u>Description</u>	<u>Results</u>
Hardness (Shore D)	70-80
% Elongation at break	25-30
Tensile strength at break	14-15

PACKAGING AND STORAGE

SAF-30 (Tube)	16.57 fluid ounces
(12) per carton	(60) per pallet

For maximum shelf life, keep in a cool and dry area where temperature does not exceed (68 degrees F or 20 Celsius)

Shelf life is 6 months in unopened original packaging.

WORKING TIME AND COVERAGE

<u>SAF-30 Version</u>	<u>Working Time</u>	<u>Cure Time</u>
SAF-30 (5)	2 min	5 min
SAF-30 (15)	6 min	15 min
SAF-30 (45)	20 min	45 min
SAF-30 (LOT)	30 min	55 min

COVERAGE

1/4" wide bead	approximate	40 lf
1/2" wide bead	approximate	20 lf



INSTALLATION

SAF-30 ADHESIVE comes in a two part tube with mixing stick. Use a two part sealant gun similar to a Cox dual component applicator model #M400XMR.

AVAILABILITY

SAF-30 ADHESIVE is available from the manufacturer, vendors, or factory trained contractors.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

HYDRO-GARD LLC • 18340 Yorba Linda Blvd. Suite 107, Box 304, Yorba Linda, Ca 92886

Tel 562/ 944-7030 • Fax 562/ 944-6402 • www.hydro-gard.com