# **HYDRO-FLASHING**





## PRODUCT DESCRIPTION

Hydro-Flashing is a PVC Thermoplastic sheet membrane designed for flashings the HYDRO-PRUFE® PVC waterproofing system. It is made of the same unreinforced PVC but in a 60 mil thickness. It can be used to flash penetrations, drains, wall flashings and any other detail work needed to complete the waterproofing system.

## PRODUCT NUMBERS AND COLORS

Standard Color is: White and Grey

## PHYSICAL PROPERTIES

<u>Description</u>	Test Method	Results
Tensile Strength	ASTM D638	1500 psi
Elongation	ASTM D638	250/200%
Tear Resistance	ASTM D1004	10
Laminated Bond ST.	ASTM D413	24
Low Temp Bend	<b>ASTM D2136</b>	-40
Heat Aging	<b>ASTM D4434</b>	90
Water Absorption	ASTM D570	3.0
Flammability	ASTM D568	SE
Seam Strength	ASTM 751	75%
Dimensional Stability	ASTM 1204	0.1
Accelerated Weather	ASTM 4434	No cracking

# PRODUCT DATA

<u>Thickness</u>	Roll/Width	Roll/Length
60 Mil	6", 12", 18", 24", 36"	100'

# **PACKAGING**

Contact Manufacturer for shipping information

## INSTALLATION

Hydro-Flashing is installed by factory trained contractors who have passed the installation guidelines set forth by the manufacturer. And who have passed the manufacturers rigid qualification requirements.

## **AVAILABILITY**

Hydro-Flashing is available from the manufacturer, vendors, or factory trained contractors.

#### WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

#### **MAINTENANCE**

Hydro-Flashing systems require no maintenance. Although the systems are subject to damage, it is recommended that the specifier contact the manufacturer to insure that the system is approved for use by the manufacturer.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit <a href="www.hydro-gard.com">www.hydro-gard.com</a>. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.