

GARD-DECK 9113 PRIMER



Gard-Deck 9113 Primer is a waterborne modified acrylic primer specifically designed as a bleed blocking primer over modified bitumen and asphalt based Roofs prior to the application of **HP-Liquid flashing 9800 membrane**

RECOMMENDED USES

- Substrate primer prior to **HP-Liquid flashing 9800**
- Substrate primer for concrete, PVC membrane or **Hydro-Tuff HFA**

COLORS

Light Grey

PACKAGING

5 gallon pail (36 pails per pallet)

1 gallon pail (4 per box) (144 cans per pallet)

REQUIREMENTS

Gard-Deck 9113 Primer is a water based acrylic adhesive primer which should be applied only by trained or manufacturer approved contractors familiar with the properties of this material.

EQUIPMENT

Gard-Deck 9113 Primer is designed for airless or conventional spray equipment. It can also be applied using an airless sprayer, brush, or phenolic resin core roller.

APPLICATION

Material may separate during storage, mix before using. **Gard-Deck 9113 Primer** application rates will vary depending on substrates. When applied to areas that retain water for 48 hours or more, service life may be diminished and adhesion failure can be expected. **Gard-Deck 9113 Primer** can be applied with airless spray equipment, brush, or roller.

Clean up can be accomplished with either water or mineral spirits.

The preceding instructions can be considered guidelines only.

MIXING

Gard-Deck 9113 Primer should be thoroughly blended using a mechanical mixer at slow speed or for at least 5 minutes if mixing by hand.

TECHNICAL DATA

Coverage Rate*	New Asphalt Membrane (<5 years) - 0.75 gallon per 100 square feet Aged Asphalt Membrane (< 5 years) - 0.5 gallon per 100 square feet Granule surface (>5 years) - 0.5 gallon per 100 square feet
Specific Gravity	1.24
Service Temperature	200°F (93°C)
Total solids by weight ASTM D2369	56 ± 2%
Total solids by volume ASSTMD2697	39 ± 2%
Viscosity at 75°F (24°C) Part A & B Combined	300-400 cps
Volatile organic compound, ASTM D2369-81	1 g / L
Dry Time	2 hours
Recoat Time	4 hours
Time to Topcoat with Acrylic	4 hours
Time to Topcoat with Silicone	4 hours
*More may be required on granule alligatored or irregular surfaces. Two coats may be needed for complete coverage.	

PERSONAL PROTECTION

Gard-Deck 9113 Primer is atomized into a very fine particle distribution during spray application, it is essential that a maximum effort is made to protect spray mechanic and others near the workplace from undue exposure. The best form of protection against organic solvents is the use of Type C organic vapor cartridge respirators. To prevent excessive skin contact with the sprayed product, we recommend using fabric coveralls and neoprene or other resistant gloves. Wear safety glasses or OSHA approved protective goggles.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

GARD-DECK 9113 PRIMER



JOB SITE PROTECTION

Overspray from **Gard-Deck 9113 Primer** can carry considerable distances and attention should be given to the following:

Post warning signs a minimum of 100 feet from the work area

Cover all intake vents near the work area

Minimize or exclude all personnel not directly involved with the spray application.

No welding, smoking, or open flames.

Have CO2 or other dry chemical fire extinguisher available at the job-site.

Provide adequate ventilation

SHELF LIFE AND STORAGE

The shelf life of **Gard-Deck 9113 Primer** is 12 months from the date of manufacturing when stored in its original unopened container at temperatures between 50-75°F (10-24°C). Keep containers closed and store away from direct sunlight, heat, sparks, open flame, and moisture.

FREIGHT CLASSIFICATION

Liquid Plastic Material - NOIBN

HEALTH AND SAFETY

Hydro-Gard is committed to the health and safety of our customers. **Hydro-Gard** products shall only be installed by certified contractors. Applicators are required to follow all proper handling, safety and installation procedures. Safety Data Sheets (SDS) are available on this material. Any individual who may come into contact with these products should read and understand the SDS.

VAPOR INHALATION

Effects of overexposure to vapor are characterized by nasal and respiratory irritation, dizziness, nausea, headache, fatigue, possible unconsciousness or even asphyxiation. Vapor inhalation problems are characterized by coughing, shortening of breath and tightness in chest. Anyone exhibiting these types of symptoms should be immediately removed from the workplace and administered oxygen or fresh air. If the condition is prolonged or extreme **SUMMON EMERGENCY TRAINED MEDICAL ATTENTION IMMEDIATELY.**

SKIN CONTACT

Skin contact with liquid components can result in a rash or other irritation. Wash affected skin area with water. Wipe residual liquid from the skin with a clean cloth, then wipe the affected area with 30% solution of rubbing alcohol. Follow the alcohol wipe with repeated washing's with soap and water. If a rash or other irritation develops, see a physician.

EYE CONTACT

Eye contact with liquid or sprayed components can result in corneal burns or abrasions. Upon exposure, eyes should be flushed with water for an extensive period. **SUMMON EMERGENCY TRAINED MEDICAL ATTENTION IMMEDIATELY.**

TECHNICAL SERVICES

Additional information such as brochures, technical assistance, and management services are also available from a **Hydro-Gard** Technical Department.

Please read all information in the general guidelines, technical data sheets, application guide, and safety data sheets (SDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local Hydro-Gard® representative or visit our website for current technical data and instructions. **DISCLAIMER:** All guidelines, recommendations, statements and technical data contained herein are based on information and tests that Hydro-Gard® believes to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the user's responsibility to satisfy himself, by his own information and tests, to determine suitability of the product for his own intended use, application and/or situation and user assumes all risk and liability resulting from his use of the product(s). Hydro-Gard® does not suggest or guarantee that any hazards listed herein are the only ones that may exist. Hydro-Gard® shall not be liable to the user or any third party for any injury, loss, damage, or costs directly or indirectly resulting from use of, or inability to use, the product(s). Recommendations or statements, whether verbal or in writing, other than those contained herein shall not be binding upon Hydro-Gard®, unless in writing and signed by an authorized corporate officer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and Hydro-Gard® makes no claim that these tests or any other tests, accurately represent all environments. Not responsible for typographical errors.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. **HYDRO-GARD** accepts no responsibility for the results obtained through application of this product. **HYDRO-GARD** reserves the right to update information without notice.