GARD-DRAIN® 400 RB-T



PRODUCT DESCRIPTION

Gard-Drain® 400RB-T is a prefabricated drainage medium designed to manage water around foundations, planting zones, green roofs or any other areas where root resistance is needed.Gard-Drain® 400RB-T is a high flow rate drainage medium utilizing a dimple core design with a root resistant spunbond nonwoven filter fabric which prevents roots from entering the drainage core. The filter fabric also prevents fines from soil and other particles from entering the drainage core.Gard-Drain® 400RB-T can be used in vertical and horizontal applications.

PRODUCT NUMBERS AND COLORS

Standard Color is: Black

PHYSICAL PROPERTIES

| Description | Test Method | Results |
|----------------------------------|--------------------------|-----------------------------------|
| Compressive Strength Thickness | ASTM D1621 ASTM D5199 | 15,000 psf .44 in |
| Core Flow Rate | ASTM D4716 | 21 gpm/ft width |
| Fabric Flow Rate Fabric Puncture | ASTM D4491 ASTM D6241 | 70 gpm/ft ² 315 lbs |
| AOS | ASTM D6241 ASTM D4751 | 70 US Sieve |
| Grab Tensile | ASTM D4632 | 150 lbs |
| Grab Elongation | ASTM D4632 | 60% |
| Recycled Content | | 77% |

PRODUCT DATA

| Roll Weight | Roll/Width | Roll/Length |
|-------------|------------|-------------|
| 43 lbs | 48" | 50' |

PACKAGING

6 Rolls per pallet

INSTALLATION

Gard-Drain® 400RB-T is installed in vertical and horizontal applications. Seams shall be overlapped and secured per manufacturers details. If installed over waterproofing membranes contact membrane manufacturer for preferred method.

AVAILABILITY

Gard-Drain® 400RB-T is available from the manufacturer, vendors, or factory trained contractors.

WARRANTY

Gard-Drain should not be used as an exposed wearing surface. Limit UV exposure to a maximum of 14 days.

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

MAINTENANCE

Gard-Drain® 400RB-T systems require no maintenance.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.