SDS SHEET



[In accordance with the regulation no 1907/2006 (Reach) and 453/210]

5	, , , , , , , , , , , , , , , , , , ,
SECTION 1	Identification
Product identifier	Gard-Deck ® 800R
Other means of identification	Not determined
Recommended use:	Coating
Manufacturer:	Hydro-Gard, LLC
Address:	18340 Yorba Linda Blvd, Suite 107, Box 304, Yorba Linda, CA 92886
Telephone / Fax	562/944-7030 / Fax: 562/944-6402
Email competent person	saras@hydro-gard.com
Further information provided by	Sara Sears, 562/944-7030
In aid and On ill I and a Fina	CUENTREC Day on Night

Incident Spill, Leak, Fire,

Exposure, or Accident

CHEMTREC Day or Night

1-800-424-9300 / +1 703-527-3887 CCN 825652

SECTION 2	Hazard (s) Identification
Classification of substance or mixture	Classification according to 1272/2008/EC -Flammable Liquid 2 H225, Skin Irritant 2 H315, Skin Sensitive 1 H317, Eye Irritant 2 H319, STOT SE 3 H335. Causes skin irritation.
Physical Hazards	Highly flammable liquid and vapor.
Health Hazards	May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.
Environmental hazards	Not classified
Label elements	
Signal Word	Danger
Product Identifier	Contains Methyl Methacrylate, 2-ethylhexyl acrylate, butyl methacrylate
Hazard Statements:	

Hazard Statements:

H225 H	lighly flamm	able liquid	and v	∕apor
--------	--------------	-------------	-------	-------

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H335 May cause respiratory irritation

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces - No Smoking

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Material Name: Gard-Deck ® 800R Version: #2 Revision date: Reviewed 07/18/17 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P 314 Get medical advice/attention if you feel unwell

Other hazards: The components of this mixture do not meet the criteria for PBT or vPvB in accordance

with Annex XIII of REACH.

SECTION 3	Composition / Information on Ingredients			
Substances	Not applicable			
Mixtures	Chemical characterization: Mixtures, r	methyl methacrylate resin.		
Dangerous ingredients:				
Chemical name	Classification acc to 1272/2008/	Identifier Codes	%	
Methyl methacrylate	EC: Flam. Liquid Skin Irritant. 2H315, Skin Sens. 1 H317, STOT SE 3 H335	CAS: 80-62-6 EINECS: 201-297-1 Index Number: 607-035-00-6 Reach number: 01-2119452498-28- XXXX	25-50%	
2 - Ethylhexylacrylat	WE: Skin irrit. 2 H315, Skin Sens. 1H317, STOT SE 3 H335	CAS: 108-11-7 EINECS: 203-080-7 Index Number: 607-107-00-7 Reach Reg number: 01- 2119453158-37XXXX	10-25%	
n - Butylmethacrylat	WE: Flam-Liq. 3H226, Skin irrit 2 H315, Skin Sens. 1 H317, Eye Irrit. 2 H319, STOT SE 3 H335	CAS: 97-88-1 EINECS:202-615-1 Index Number: 607-033-00-S Reach Reg number: 01-219486934- 28-XXXX	2.5-10%	
N.N-Di-(2hydroxyethyl)-p-toluidin	WE: Acut Tox. 4 H302, skin irrit 2 H315, Eye Dam 1 H318	CAS: 3077-12-1 EINECS:221-359-1 Index Number: Reach Reg number: -	<2.5%	
Naphtha (ErdOI), Hydrodesulfuriert, schwer	WE: Flam. Liq. 3 H226, Asp. Tox. 1H304, STOT SE 3 H336, Aquatic Chronic 2 H411	CAS: 64742-82-1 EINECS:265-185-4 Index Number: 649-330-00-2 Reach Reg number: -	<1%	

SECTION 4	First - Aid Measures
General Information:	Take off contaminated clothing immediately. Move the victim to fresh air.
Inhalation:	Consult a doctor if disturbing symptoms appear. Move the victim to fresh air. Keep victim warm and calm.
Skin Contact:	Wash the contaminated skin thoroughly with plenty of water. Consult a doctor if disturbing symptoms appear.
Eye contact:	Protect the non-irritated eye, remove contact lenses. Wash the contaminated eye with plenty of water for several minutes. Avoid powerful water stream-risk of cornea damage. Consult a doctor if disturbing symptoms appear.
Ingestion:	Do not induce vomiting. Rinse mouth with water. Never give anything by mouth to an unconscious person. Consult a doctor immediately, show the container or label.
Most important symptoms and effects, both acute and delayed	The product may trigger sensitization of the skin and respiratory tract. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Extended medical treatment may be required depending on the degree of exposure and the severity of the symptoms.

Material Name: Gard-Deck ® 800R Version: # 2 Revision date: Reviewed 07/18/17

Indication of any immediate medical attention and special treatment needed:

Physician makes a decision regarding further medical treatment after thoroughly examination of the injured. Symptomatic treatment.

SECTION 5	Fire - Fighting Measures
Extinguishing media	
Suitable extinguishing media:	CO ₂ , sand, extinguishing powder. Do not use water.
Unsuitable extinguishing media:	Water jet - risk of the propagation of the flame.
Special hazards arising from the substance or mixture	During fire, the product may produce toxic fumes of carbon oxides, nitric oxides. Do not inhale combustion products, they can be dangerous for human health.
Advice for fire fighters	Highly flammable liquid and vapor. High temperature may trigger polymerization. Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

SECTION 6	Accidental Release Measures
Personal precautions, protective equipment and emergency procedures	Use personal protective measures. Ensure adequate ventilation. Avoid skin and eyes contamination. Do not breathe vapors. Keep away from sources of ignition.
Environmental precautions	Do not allow product to reach sewage system, water bodies or ground/soil. In case of release of large amounts of the product, it is necessary to take appropriate steps to prevent it from spreading into the environment. Notify relevant emergency services.
Methods and material for containment and cleaning up	Collect with liquid absorbing materials (e.g. soil, sand, silica, universal binding agent, vermiculite, etc.) and place it in labeled containers. Do not flush with water or aqueous cleaning agents. Collect in a suitable container. Treat the collected material as waste. Clean the contaminated place and ventilate it.
Reference to other sections:	Appropriate conduct with waste product - Section 13. Personal protective equipment - see Section 8.

SECTION 7	Handling and Storage
Precautions for safe handling	Handle in accordance with good occupational hygiene and safety practices. Avoid contact with skin and eyes. Do not breathe vapors. Before break and after work wash hands. Use only in accordance with the identified purpose. Keep away from ignition sources. Do not eat, drink or smoke when using this product. Protect against electrostatic charges. Use only non-sparking tools.
Conditions for safe storage, including any incompatibilities	Keep in a dry, cool and well-ventilated area. Keep away from high temperatures and direct sunlight. Temperature recommended for storage: 41 $^{\circ}F$ - 77 $^{\circ}F$ (5 - 25 $^{\circ}C$). Keep containers tightly sealed. Store only outside or in explosion proof rooms.
Specific and use (s)	No information about other use than those mentioned in Section 1
SECTION 8	Exposure Controls / Personal Protection
Control Parameters	Components with Community workplace exposure limits:

Metyl methacrylate (50-100%) CAS 80-62-6	Limit value - Eight hours	50 ppm
Metyl methacrylate (50-100%) CAS 80-62-6	Limit value - Short term	100 ppm
Legal basis: Commission Directive 2006/15/EC Please check any national occupational exposure limit values in your country		

Material Name: Gard-Deck ® 800R Version: # 2 Revision date: Reviewed 07/18/17 Page 3 of 9 Issued date: 06/01/15

DNEL and PNEC for methyl methacrylate (CAS 80-62-6)

DNEL	ORAL	INHALATION	DERMAL
Workers, long-term, local effects	1	210 mg/m ³	1,5 mg/cm ³
Workers, long-term, systemic effects	1	210 mg/m ³	13,67mg/kg KG/day
Workers, acute, local effects	1	2	1,5 mg/cm ³
Workers, acute, systemic effects	1	2	-
Consumers, long-term, local effects	1	105 mg/m ³	1,5 mg/cm ³
Consumers, long-term, systemic effects	1	74,3 mg/m ³	8,2mg/kg KG/Tag
Consumers acute, local effects	1	2	1,5 mg/cm ³
Consumers, acute, systemic effects	1	2	

1) low oral toxicity: DNEL not calculated

2) Long-term DNEL

Comment	PNEC	
PNEC Freshwater	0,94 mg/l	
PNEC Seawater	0,094 mg/l	
PNEC Sediment	5,74 mg/kg	
PNEC Soil	1,47 mg/kg	

Exposure Controls	Use the product in accordance with good occupational hygiene and safety practices. Do not eat, drink or smoke when using the product. Before break and after work wash hands carefully. Keep away from foodstuffs, beverages and food. Take off contaminated
	clothing immediately. Avoid contact with skin and eyes. Protective clothing should be

Hand protection

Only use chemical-protective gloves with CE-labeling of category III: Nitrile rubber, Butyl rubber. Recommended thickness of material: >/= 0,5 mm



The section of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, th resistance of the glove material can not be calculated in advance and has therefore to be check prior to the application. www.gisbau.de/service/epoxi/expotab.html

Eye protection

Use tightly fitting protective glasses

stored separately.



Respiratory protection



Recommended filter device for short term use; Combination filter A-P2

Body Protection	Protective clothing necessary
	Applied personal protective equipment must comply with requirements of the Directive 89/686/EC. The employer is obliged to provide protective equipment relevant to performed activities and in accordance with all quality requirements, including its maintenance and cleaning.
Environmental exposure controls	Do not allow large quantities of the product to contaminate ground water, canalization, sewages or soil.

SECTION 9 Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State: Liquid

> Color: Blue

Odor Characteristic

Odor threshold Not determined

> рН: Not determined

Melting point/freezing point: Not determined

Initial boiling point and boiling range: 212 °F (100°C)

> Flash point: 50° F (10°C) (MMA, DIN 51755)

Ignition Temperature: 806°F (430°C)

Evaporation Rate: Not Determined

Flammability (solid, gas) Not Applicable

Upper/Lower Flammability or Explosive Limits 12,5 Vol %/0,8 Vol.%

> Vapor Pressure (68°F (20°C)) 38,7 hPa

> > Vapor Density Not Determined

Density (68°F (20°C)) 1 g/cm³

Solubility (ies)(water) max 16 g/l

Solubility(ies): (organic solvents) Soluble in many organic solvents

Partition Coefficient: n-octanol/water: Not Determined

> Auto-Ignition Temperature: Not Applicable

Decomposition Temperature: Not Determined

> **Explosive Properties:** Product is not explosive. However, formation of explosive

sir/steam mixtures is possible

Oxidizing Properties: Not Determined

Viscosity:dynamic (73.4°F (23°C)) 800-1200 mPas (Brookfield Spindel 63,12 U/min)

Other Information: VOC 0.01%

Page 5 of 9 Revision date: Reviewed 07/18/17 Issued date: 06/01/15

SECTION 10 Stability and Reactivity

Reactivity High temperature may trigger polymerization.

Chemical stability The product is stable under normal conditions of use and storage.

Possibility of hazardous

reactions

Violent reactions with strong alkalis and oxidizing agents. Reacts with amines.

Condition to avoid Avoid heat sources and direct exposure to sunlight.

Incompatible materials Acids, strong oxidizing agents

Hazardous decomposition

products

In the event of fire: toxic gases and vapors, inflammable gases/vapors

SECTION 11 Toxicological Information

Information on toxicological effects

Acute toxicity:

Methylmethacrylat, CAS 80-62-6			
Oral	LD ₅₀	>5000 mg/kg	(rat)
Dermal	LD ₅₀ DNEL (Langzeit)	>5000 mg/kg 74,3 mg/m³	(rab)
Inhalativ	LD ₅₀ DNEL (Langzeit)	29,8 mg/l/4h 210 mg/m³	(rat)
N,N-Bix-(2-hydroxypropyl)-ptouluidin, CAS 938668-48-3			
Oral	LD ₅₀	100 mg/kg	(rat)

Toxicity of the product:

Acute Toxicity ATEmix (oral) >2000 mg/kg. Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation Causes skin irritation.

Serious Eye

Damage/Irritation

Causes serious eye irritation

Respiratory or skin

Sensitization

May cause an allergic skin reaction

Germ Cell Mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation

Based on available data, the classification criteria are not met. **Aspiration Danger**

SECTION 12 Ecological Information (non-mandatory)

Toxicity

Aquatic toxicity:

Methylmethacrylat, CAS 80-62-6			
Algae toxicity	EC ₅₀	>110 MG/1/72h	Selenastrum capricornutum, (OECD 201)

Material Name: Gard-Deck ® 800R

Page 6 of 9 Revision date: Reviewed 07/18/17 Issued date: 06/01/15

Bacterial toxicity	EC ₃ 100 mg/l/16h	Pseudomonas putida	
Daphnia toxicity	EC ₅₀ 69 mg/l/48h NOEC 37mg/l	Daphnia magna, (OECD 202) Daphnia magna, (OECD 202 Part 2, 21d)	
Fish toxicity	LC ₅₀ > 79 mg/l/96h NOEC 9,4 mg/l	Onchorhynchus mykiss, (OECD 203) Danio rerio, (OECD 210 fish early life stage test)	
BSB5	0,14 g/g		
N, N-Bis-(2-hydroxypropyl)-p-toluidin, CAS 38668-48-3			
Daphnia toxicity	EC50 28.8 mg/l	Daphnia magna	
Fish toxicity	LC ₅₀ 17 mg/l	Danio rerio	
BSB5	11 mg O ₂ / g		

Persistence and degradability

Easily biodegradable

Bioaccumulative potential Low bioaccumulative potential

Mobility in soil No further relevant information available

Results of PBT and vPvB

assessment

Not applicable

SECTION 13	Disposal Consideration (non-mandatory)
Waste treatment methods	Disposal methods for the product: disposal in accordance with the local legislation. Store residues in original containers.
Disposal methods for used packing:	Reuse/recycle/liquidate empty containers in accordance with the legislation in force. Only containers completely empty can be recycled.
	Legal basis: Directive 2008/98/EC, 94/92/EC
European Waste catalogue:	
08 00 00	Wastes FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 02 00	wastes from MFSU of other coatings (including ceramic materials
08 02 99	wastes not otherwise specified

SECTION 14	Transport Information (non-mandatory)	
UN Number		
ADR, IMDG, IATA	1993	
UN proper shipping name		
ADR	1993 Flammable liquid, N.O.S.	
IMDG, IATA	1993 Flammable Liquid, N.O.S.	
Transport hazard class(es)		
ADR	3 (F1) Flammable liquids	
IMDG, IATA	3 Flammable liquids	



Packing Group III

Environmental Hazards Marine Pollutant: No

Special Precautions for User Kemier-Number: 33

EMS-Number: F-E,S-E

Transport Bulk According to Annex II of MARPOL 73/78 and the IBC Code - Not applicable

Transport/Additional information: ACR

Limited quantities (LQ): 5 L

Transport category: 3

Tunnel restriction code: D/E

UN "Model Regulations": UN1993, Flammable Liquid, N.O.S., 3, III

SECTION 15 Regulatory Information (non-mandatory)

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorizat6ion and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC as amended.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 as amended.

<u>Council Directive 67/548/ECC</u> of 27 June 1967 on the approximation of laws, regulations and administrative provisions relating to the classification, packaging and labeling of dangerous substances.

<u>Directive 1999/45/EC</u> of the European Parliament and of the Council of 31 May 1999 concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labeling of dangerous preparations.

Commission Regulation (EC No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labeling and packaging of substances and mixtures.

Commission Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH). Directive 208/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives.

European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste.

<u>Chemical safety assessment</u> A Chemical Safety Assessment is not required for mixtures

SECTION 16 Other Information, Including date of preparation or last revision

This data is based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Clarification of aberrations and acronyms

PBT Persistent, Bioaccumulative and toxic substance

vPvB Very Persistent, very Bioaccumulative substance

ADR Accord to European sur le transport des merchandisers dangeroses par Route(European

Agreement concerning the International Carriage of Dangerous Goods by Rail)

Material Name: Gard-Deck ® 800R

Version: # 2 Revision date: Reviewed 07/18/17 Issued date: 06/01/15

Page 8 of 9

IMDG International Maritime Code fro Dangerous Goods

IATA International Air Transport Association

ICAO International Civil Aviation Organization

GHS Globally Harmonized System of Classification and Labeling of Chemicals

GefStoffV Ordinance on Hazardous Substances, Germany

LC50 Lethal concentration, 50 percent

LD50 Lethal dose, 50 percent

Other Data Classification was based on data on hazardous substances calculation method under the

guidance of Regulation 1272/200//EC (CLP).

The information and recommendations provided in this Safety Data Sheet are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information supplied upon the condition that the persons receiving said information will make their own determination as to its suitability for their particular purpose prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representation or warranties, either expressed or implied. Including the merchantability or fitness for a particular purpose are made herein with information contained herein is deemed to be reliable, conservative and accurate. Hydro-Gard, LLC reserves the right to change the design, specification or any other features at any time, without notice, while otherwise maintaining regulatory compliance.

End of Safety Data Sheet

Material Name: Gard-Deck ® 800R Page 9 of 9 Version: #2 Revision date: Reviewed 07/18/17 Issued date: 06/01/15