HDPE - PROTECTION ROLL



PRODUCT DESCRIPTION

HDPE protection roll is a geo-membrane manufactured for the protection of the HYDRO-PRUFE® PVC waterproofing systems. If the HYDRO-PRUFE® systems are not covered by other approved overlayment then the HDPE is required. It can be used in vertical applications or horizontal applications. It comes in 30 mil, 40 mil, 60 mil and 80 thicknesses. The HDPE protection roll is highly puncture resistant.

PRODUCT NUMBERS AND COLORS

Standard Color is: Black

Description

PHYSICAL PROPERTIES

Description	1 est iviethou	Results
Tensile Properties (@ Break)	ASTM D-6693	30 mil / 122 40 mil / 162 60 mil / 243 80 mil / 326
Elongation (@ Break)	ASTM D-6693	30 mil / 700 40 mil / 700 60 mil / 700 80 mil / 700
Tear Resistance (min)	ASTM D-1004	30 mil / 21/lbf 40 mil / 28/lbf 60 mil / 42/lbf 80 mil / 57/lbf
Puncture Resistance	ASTM D4833	30 mil / 60/lbf 40 mil / 80/lbf 60 mil / 122/lbf

Test Method

Regulte

INSTALLATION

The HDPE protection roll is loose laid over the HYDRO-PRUFE® membrane. It can be spot welded or fully welded at the seams. If concrete or shotcrete is placed directly against the HDPE ensure that all seams are secured so no concrete enters the HDPE seams. When installing vertically to protect the HYDRO-PRUFE® waterproofing system secure temporally in place but ensure not to penetrate the waterproofing system. Contact manufacturer for further information.

AVAILABILITY

HDPE protection roll is available from the manufacturer, vendors, or factory trained contractors..

PACKAGING

Standard rolls come in 22.3 feet wide and lengths from 100' up to 300'. 5' wide rolls can be custom ordered. Contact manufacturer for specific sizes.

WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

MAINTENANCE

HDPE requires no maintenance.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

80 mil / 155/lbf