

HYDRO-FLASHING (AR)

FLASHING SYSTEM



PRODUCT DESCRIPTION

Hydro-Flashing(AR) is a flexible asphalt resistant PVC Thermoplastic sheet membrane designed for flashing the HYDRO-PRUFE® PVC waterproofing system when asphalt or bitumen may come in contact with the PVC flashing. It is made of treated unreinforced PVC but in a 60 mil thickness. It can be used to flash penetrations, drains, wall flashing, and any other detail work needed to complete the below grade waterproofing system. It is also used to interface the HYDRO-PRUFE® PVC membrane with HYDRO-TUFF (HFA) rubberized asphalt membrane in typical below grade to horizontal waterproofing traditions.

PRODUCT NUMBERS AND COLORS

Standard Color is: Black

PHYSICAL PROPERTIES

Description	Test Method	Results
Tensile Strength	ASTM D638	1500 psi
Elongation	ASTM D638	250/200%
Tear Resistance	ASTM D1004	10
Laminated Bond ST.	ASTM D413	24
Low Temp Bend	ASTM D2136	-40
Heat Aging	ASTM D4434	90
Water Absorption	ASTM D570	3.0
Flammability	ASTM D568	SE
Seam Strength	ASTM 751	75%
Dimensional Stability	ASTM 1204	0.1
Accelerated Weather	ASTM 4434	No cracking

PRODUCT DATA

Thickness	Roll/Width	Roll/Length
60 Mil	6"	100'
60 Mil	12"	100'
60 Mil	18"	100'
60 Mil	24"	100'
60 Mil	36"	100'

PACKAGING

Contact Manufacturer for shipping information

INSTALLATION

Hydro-Flashing (AR) is installed by factory trained contractors who have passed the installation guidelines set forth by the manufacturer. And who have passed the manufacturers rigid qualification requirements.

AVAILABILITY

Hydro-Flashing(AR) is available from the manufacturer, vendors, or factory trained contractors.

WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

MAINTENANCE

Hydro-Flashing(AR) systems require no maintenance. Although the systems are subject to damage, it is recommended that the specifier contact the manufacturer to insure that the system is approved for use by the manufacturer.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

HYDRO-GARD LLC • 18340 Yorba Linda Blvd. Suite 107, Box 304, Yorba Linda, Ca 92886

Tel 562/ 944-7030 • Fax 562/ 944-6402 • www.hydro-gard.com