

# HYDRO-TUFF® CS® CS-100



## PRODUCT DESCRIPTION

Hydro-Tuff® CS-100 is a SBS modified fiberglass granulated cap sheet used to be imbedded into the Hydro-Tuff® HFA membrane while the membrane is still warm and sticky. It is the heaviest SBS version of protection of the Hydro-Tuff® protection layers. Hydro-Tuff® CS-100 is intended to be used as a protection material for the Hydro-Tuff® HFA. Hydro-Tuff® CS-100 is UV resistant and provides superior protection of the waterproofing membrane.

## PRODUCT NUMBERS AND COLORS

Standard Color is: Black / with sanded surface

## TYPICAL PROPERTIES

<u>Description</u>	<u>Results</u>
Roll Dimension	39"W x 34' L
Square Feet	100 sf
Roll Weight	100 lbs
Weight per Square	100 lbs
Thickness	120 mils

## PACKAGING

Pallet: 25 rolls  
Truck Load: 400 rolls

## INSTALLATION

The Hydro-Tuff® CS-100 is set in the warm and sticky Hydro-Tuff® HFA membrane. Overlap side and end laps a minimum of 3" and ensure laps are well adhered. Hydro-Tuff® CS-100 can be exposed to prolonged periods of UV exposure. Consult with manufacturer for additional information.

## AVAILABILITY

Hydro-Tuff® CS-100 is available from the manufacturer, vendors, or factory trained contractors.

## WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

## MAINTENANCE

Hydro-Tuff® CS-100 requires no maintenance.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit [www.hydro-gard.com](http://www.hydro-gard.com). HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.

**HYDRO-GARD LLC** • 18340 Yorba Linda Blvd. Suite 107, Box 304, Yorba Linda, Ca 92886

Tel 562/ 944-7030 • Fax 562/ 944-6402 • [www.hydro-gard.com](http://www.hydro-gard.com)