GARD-FLEX



FIBER REINFORCED POLYMER MODIFIED BITUMEN

PRODUCT DESCRIPTION

Gard-Flex is a fiber reinforced polymer modified bitumen liquid flashing compound in a one part single component. The flashing compound comes in a thick paste form so it can be used in vertical and horizontal applications. Gard-Flex is also solvent free. It is used with Hydro-Ultra Mat B series as a typical mastic compound. Once applied in it's paste form it will cure to a flexible rubber type of membrane.

PRODUCT NUMBERS AND COLORS

Standard Color is: Black

PROPERTIES

- One component
- Water based
- Solvent Free
- Polymer Modified Bitumen
- Service Temperature > 40°F to 90°F
- Consistency Pasty Trowel Grade viscosity

PACKAGING

Buckets 30 kg / 7.92 gallons Pallets 18 pails / per pallet

INSTALLATION

Gard-Flex is installed by factory trained contractors who have passed the installation guidelines set forth by the manufacturer. And who have passed the manufacturers rigid qualification requirements.

AVAILABILITY

Gard-Flex is available from the manufacturer, vendors, or factory trained contractors.

WARRANTY

Warranties are available upon successful installation and range in coverage. Contact the manufacturer for further information concerning warranties.

MAINTENANCE

Gard-Flex systems require no maintenance. Although the systems are subject to damage, it is recommended to be inspected annually.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience. For the most up to date information, please visit www.hydro-gard.com. HYDRO-GARD accepts no responsibility for the results obtained through application of this product. HYDRO-GARD reserves the right to update information without notice.